

Roller Rocker Application Guide

CHEVROLET SMALL BLOCK 23°			
ENGINE TYPE	STREET TERRA	YELLA TERRA	PLATINUM
FACTORY IRON 461-491 BOWTIE iron & alloy 23° ALLPRO 215 23° BRODIX track 1 DART , Dart II, Iron eagle 23° WORLD sportsman II, conquest S/R Torquer 305 Torquer EDELBROCK Victor jnr PRO Iron lightning All with 1.770" stud centres	STUD MOUNT (1.5) 3/8" (1.6) 3/8" (1.5) 7/16" (1.6) 7/16" ST 2000 ST 2004 ST 2001 ST 2005	STUD MOUNT (1.5) 3/8" (1.6) 3/8" (1.5 x 1.6) 3/8" (1.5) 7/16" (1.6) 7/16" (1.5 x 1.6) 7/16" YT 5000 YT 5019 YT 5023 YT 5001 YT 5002 YT 5017	TWIN SHAFT 7/16" (1.55 x 1.55) (1.6 x 1.6) (1.6 x 1.5) (1.65 x 1.55) * 150" o/s inlet SINGLE SHAFT 7/16" (1.5 x 1.5) (1.6 x 1.6) (1.6 x 1.5) Also suitable for TFS Twisted Wedge YT 6008 YT 6009 *YT 6341 *YT 6613 YT 6355 YT 6356 YT 6357
AFR 180-210 23° Original *1.770" stud centres		STUD MOUNT (1.5) 7/16" (1.6) 7/16" (1.5 x 1.6) 7/16" YT 5001 YT 5002 YT 5017	TWIN SHAFT 7/16" (1.55 x 1.55) (1.65 x 1.55) *.250" o/s inlet *YT 6618 *YT 6619
AFR 227 23° Original *1.770" stud centres		STUD MOUNT (1.5) 7/16" (1.6) 7/16" (1.5 x 1.6) 7/16" YT 5001 YT 5002 YT 5017	TWIN SHAFT 7/16" (1.5 x 1.5) (1.6 x 1.5) (1.65 x 1.55) *.200" o/s inlet *YT 6615 *YT 6616 *YT 6617
DART Pro 1 23° * 1.770" stud centres		STUD MOUNT (1.5) 7/16" (1.6) 7/16" (1.5 x 1.6) 7/16" YT 5001 YT 5002 YT 5017	TWIN SHAFT 7/16" (1.5 x 1.5) (1.6 x 1.5) (1.6 x 1.6) *.150" o/s inlet *YT 6620 *YT 6621 *YT 6623
DART 220 23°			TWIN SHAFT 7/16" (1.6 x 1.5) *.275" o/s inlet *YT 6622
CANFIELD avenger WORLD MOTOWN AFR 220 BROWNFIELD 195 *1.770" stud centres			TWIN SHAFT 7/16" (1.55 x 1.55) (1.6 x 1.5) (1.65 x 1.55) *.265" o/s inlet *YT 6326 *YT 6327 *YT 6343
BRODIX -8, -10, -10x, -11 BOWTIE alloy 23° PONTIAC nascar 23° RACER PRO RP216 std port AFR ELIMINATOR * 1.810" stud centres			TWIN SHAFT 7/16" (1.55 x 1.55) (1.6 x 1.6) (1.6 x 1.5) YT 6308 YT 6325 YT 6338
PONTIAC / CHEV 23deg semi fin p/rod holes RACER PRO RP216RI * 1.810" stud centres			TWIN SHAFT 7/16" (1.6 x 1.5) (1.6 x 1.6) *.275" o/s inlet *YT 6342 *YT 6340
BRODIX 18X			TWIN SHAFT 7/16" (1.5 x 1.5) (1.6 x 1.5) YT 6315 YT 6316

For more information see offset listing page 13.

NOTE: To machine for screw in studs or Platinum Rockers remove .320" from Rocker pads, drill and tap 7/16" UNC, fit studs and gaskets sold separately

NOTE: Studs and guide plates not required for Platinum Rockers. Platinum Twinshaft Rockers Notched for 1.550" Springs